

***Perfect Doorphone choice for daily life***

Akuvox's Audio Doorphone R23P is an open, non-proprietary IP-based door station for two-way communication and remote entry control. It is a perfect complement to any SIP system and offers new possibilities to effectively control entry to your premises.

***At a Glance***

- Vandal resistant body, with a flush button;
- PoE (IEEE802.3af, Power-over-Ethernet);
- Two-way audio communication over IP networks with Echo Cancel feature;
- Complies with SIP standard for easy integration in every SIP capable PBXes;



**Physical & Power**

- |  |   |
|--|---|
| • Front panel: Aluminum                    | • Power out: 12V/400mA                        |
| • Button: 1 call button                    | • 802.3af Power-over-Ethernet                 |
| • Wiegand port: Support                    | • 12V DC connector (if not using PoE)         |
| • RS485 port: Support                      | • Water-proof & Dust-proof: IP65              |
| • Relays out: 2                            | • Installation: Flush-mounted or Wall-mounted |
| • Inputs: 3                                | • Flush-mounted DIM: 213x124x68mm             |
| • Microphone: -40dB                        | • Wall-mounted DIM: 190x110x40mm              |
| • Speaker: 8Ω / 2W                         | • Working Humidity: 10~90%                    |
| • Ethernet port: RJ45, 10/100Mbps adaptive | • Working Temperature: -20°C ~ +55°C          |
|  | • Storage Temperature: -40°C ~ +70°C          |